

SUNSTREAM

SUNLIFT SLX





**FIRST BOAT
IN THE WATER
WINS.**

SUNSTREAM HELPS YOU ENJOY YOUR BOAT MORE.

Boating is our passion and, like you, we envisioned a future that minimized the hassles and frustrations of getting your boat in and out of water, accessing the hull and covering the boat. For over 25 years, we've been leading the industry by elevating boating experiences all over the globe. Our award winning engineering and design continue to push the boundaries of what's possible by producing many of the world's first freestanding hydraulic boat lifts and automatic cover systems. You're invited to the future of boating.

Boat more, boat easier, boat better.



FREE-STANDING
HYDRAULIC LIFT



FREE-FLOATING
HYDRAULIC LIFT



AUTOMATIC BOAT
COVER SYSTEM



SUNLIFT SLX

SUNLIFT SLX

The Best Just Got Better.

The Sunlift SLX is the new standard in free-standing hydraulic boat lifts. Sunstream has a rich heritage of innovation and it continues to drive us today more than ever. We're boaters too and we believed boating could be more fun and less hassle. The Sunlift SLX is the culmination of meticulous engineering, unparalleled manufacturing and technological advancement.

Well designed to lift boats and drop jaws.





- 1 Adjustable Width Bunks
- 2 Adjustable Range Option
- 3 Side Shift
- 4 Stainless Steel Cylinders & Hoses

- 5 Hydraulic Boot & Scrubber
- 6 Cylinders Aligned with Frame
- 7 Soft Stop
- 8 Bronze Bushings

- 9 Stylish Domed Head Pins
- 10 Set Bolt in Leg Sleeves
- 11 Oval Cast Feet
- 12 SuperBunks™

- 13 3.25in Wide Beams
- 14 Thick Wall Aluminum Construction
- 15 Bronze Nuts
- 16 GravityLock™

FLAWLESS HULL FIT

The SunLift SLX is the only hydraulic lift that has adjustable width bunks to achieve an ideal boat fit. Additionally, the boat height over water can be set with an adjustable lifting range up to 6.5 feet. The frame can also shift laterally to minimize the distance of the boat to dock to allow safe boarding every time. Sunstream SuperBunks™ softly cradle the hull and will last for years without wear. The Superbunks™ act as spring beams, which spread the load over the entire bunk, creating a comfortable resting spot for your boat without pressure points.

SUPERIOR HYDRAULICS

The hydraulic system is the heart of a hydraulic lift and is key for reliability and performance. The SunLift SLX never compromises on durability with all stainless steel cylinders, a patented shaft boot with scrubber and scraper seal, double braid stainless hoses, and stainless fittings. The SLX has elite performance with a premium pressure balanced pump (vs a basic fixed gear pump) that has up to 20% more efficiency, higher speed, quieter sound, and does not lose lifting capacity over time. The SoftStop™ eases the hydraulic power for a smooth finish to the top position.

MODERN FRAME

The SunLift SLX modern frame has a beauty that is worthy of displaying your boat. The frame has superior stiffness with the cylinders aligned with frame, fewer bolts, and a set bolt to remove movement in the leg socket. The Sunstream SLX boasts the best range of specifications on the market, with the highest lifting range, shallowest water depth, fastest speed, and capacities to 30,000lbs. Optional Leg Jacks can give an additional 3ft of range to lakes with seasonal fluctuation. The over-center GravityLock™ gives you maximum peace of mind.



Optional bow stop shown

BLUETOOTH & APP



Sunstream's optional Bluetooth transmitter and smartphone app give you the power to lift your boat with your phone! It also gives important lift diagnostics to prevent a problem from becoming a problem. Bluetooth technology has more consistent range, and is more responsive. Built-in security features protect your boat, and 'depressurize' is ideal for seasonal users.



SWIFTSHIELD

Sunstream's SwiftShield automatic boat cover system helps you to use your boat more and protects your investment. Say farewell to the frustration that comes with traditional boat covers and hello to boating anytime you want. Be on the water in just 30 seconds with the push of a remote.

SPECIAL CONFIGURATIONS



Shallow Water
SW



Pontoon/Tritoon
Lifting with Toons
PON



Pontoon/Tritoon
Underdeck Lifting
UDK



3' Range
B3

MEDIUM Family B

LARGE Family B

X-LARGE Family C

	SLX5010B4	SLX6512B4	SLX8012B4	SLX9012B5	SLX10014B5	SLX12016B5	SLX16018C5	SLX20020C5	SLX24022C5	SLX30022C5
Capacity at Standard Range	5,000lb 2268kg	6500lb 2948kg	8000lb 3629kg	9000lb 4082kg	10000lb 4536kg	12000lb 5443kg	16000lb 7257kg	20000lb 9072kg	24000lb 10886kg	30000lb 13608kg
Standard Range	4ft 1.2m	4ft 1.2m	4ft 1.2Mm	5ft 1.52m	5ft 1.52m	5ft 1.52m	5ft 1.52m	5ft 1.52m	5ft 1.52m	5ft 1.52m
Bunk Length	10ft 3m	12ft 3.7m	12ft 3.7m	12ft 3.7m	14ft 4.2m	16ft 4.9m	18ft 5.5m	20ft 6m	22ft 6.7m	22ft 6.7m
Frame Width*	102.5in 260.3cm	102.5in 260.3cm	132.5in 336.5cm	132.5in 336.5cm	132.5in 336.5cm	132.5in 336.5cm	152.5in 387.3cm	152.5in 387.3cm	152.5in 387.3cm	152.5in 387.3cm
Frame Length**	120.5in 306cm	144.4in 366.7cm	144.8in 367.7cm	145.9in 370.5cm	169.4in 430.2cm	193.4in 491.2cm	173.6in 440.9cm	197.6in 501.9cm	221.6in 562.8cm	221.6in 562.8cm
Cylinders	2	2	2	4	4	4	4	4	4	6
Min Depth Under Keel/Skeg (typ)	7in 18cm	7in 18cm	8in 23cm	8in 23cm	8in 23cm	8in 23cm	10in 25cm	10in 25cm	10in 25cm	10in 25cm
Shallow Water Min Depth Under Keel/Skeg (typ)	0-3in 0-8cm	0-3in 0-8cm	0-3in 0-8cm	0-3in 0-8cm	0-3in 0-8cm	0-3in 0-8cm	N/A	N/A	N/A	N/A

*Frame width measured outside edges of leg sleeves

**Frame length measured front of forward crossbeam to back of rear crossbeam

Capacity at:	SLX5010B4	SLX6512B4	SLX8012B4	SLX9012B5	SLX10014B5	SLX12016B5	SLX16018C5	SLX20020C5	SLX24022C5	SLX30022C5
3ft .91m	5000lb 2268kg	6500lb 2948kg	8000lb 3629kg	N/A	N/A	N/A	N/A	N/A	N/A	N/A
4ft 1.2m	5000lb 2268kg	6500lb 2948kg	8000lb 3629kg	9000lb 4082kg	10000lb 4536kg	12000lb 5443kg	16000lb 7257kg	20000lb 9072kg	24000lb 10886kg	30000lb 13608kg
5ft 1.52m	5000lb 2268kg	6000lb 2721kg	7400lb 3357kg	9000lb 4082kg	10000lb 4536kg	12000lb 5443kg	16000lb 7257kg	20000lb 9072kg	24000lb 10886kg	30000lb 13608kg
6ft 1.82m	4500lb 2041kg	5000lb 2268kg	6000lb 2722kg	8500lb 3856kg	9000lb 4082kg	10000lb 4536kg	16000lb 7257kg	19000lb 9072kg	20000lb 9072kg	26000lb 11793kg
6.5ft 2m	4000lb 1814kg	4500lb 2041kg	5500lb 2495kg	7500lb 3402kg	8000lb 3629kg	9000lb 4082kg	16000lb 7257kg	17000lb 7711kg	18000lb 8165kg	24000lb 10886kg

With B3 Config

Cut Range

Standard Range

With AR18 Accy.

With AR30 Accy.

SUNSTREAM


SUNLIFT SLX



FLOATLIFT
Free-floating
Hydraulic Boat Lift



SWIFTSHIELD
Automatic Cover
System



SUNLIFT LEGACY
Original Hydraulic
Free-standing Lift



SUNPORT2
PWC Drive-On
Dock

BOAT MORE,
BOAT EASIER,
BOAT BETTER.

sunstreamboatlifts.com